

Diaphragm Pressure Gauges

Diaphragm with dry, FDA-compliant measuring unit made of 316 L, welded, with flush-mounted membrane

PCh 100 – 3 DG

Applications

The PCh 100 – 3 DG is suitable for the sterile process technology, which is especially applied in food and pharmaceutical industries. All the wetted parts of this diaphragm pressure gauge are made of stainless steel 1.4435 / 316 L and are completely welded. Since there is no filling fluid, this pressure gauge is equipped with an absolutely dry measuring unit. In the event of damage, the contamination of the medium due to transfer fluid from the measuring system can herewith be excluded.

Nominal case sizes 100 mm (4")

Accuracy (EN 837-3) class 1.6

Pressure ranges (EN 837-3)
-1 – 3 bar
-1 – 5 bar
-1 – 9 bar
0 – 4 bar
0 – 6 bar
0 – 10 bar

Protection type IP 54 (EN 60 529 / IEC 529)

Further information on advantages, applications, metrological features, temperature resistance and pressure ranges of all available diaphragm pressure gauge models cl. 1.6 can be found in our **model overview 3000**.



Standard Version

Connection:	e.g. Clamp ISO 2852 DN 38 other connections see page 2
Movement:	stainless steel
Dial:	aluminum, white background, black figures
Pointer:	aluminum black
Case:	bayonet ring case stainless steel 1.4301 (ventilated)
Window:	laminated safety glass
Measuring cell:	dry measuring cell DG (Dry Genic)
Wetted parts:	1.4435 / 316 L
Surface roughness of the wetted parts	$R_a < 0.8 \mu\text{m}$
Permissible Temperature:	ambience: -20 ... +60 °C (-4...140 °F) medium: +150 °C (+302 °F)

Special Versions (Upon Request)

- 3-A approval
- Other pressure ranges
- Other temperature ranges
- Wetted parts made of Inconel

Ordering Information (Model Construction)

Please specify in your order:

Basic model:	PCh
Nominal case size:	100
Ordering code of the wetted parts:	- 3
Pressure range:	according to EN 837-3 e.g. 0 – 4 bar
Connection:	e.g. Clamp ISO 2852 DN 38

Example for Ordering Information:

- PCh 100 – 3 DG, 0 – 10 bar, Clamp ISO 2852 DN 38



Sales and Export South, West, North
ARMATURENBAU GmbH
Manometerstraße 5 • D – 46487 Wesel-Ginderich
Tel.: +49 2803 9130 – 0 • Fax: +49 2803 1035
armaturenbau.com • mail@armaturenbau.com

Subsidiary Company, Sales and Export East
MANOTHERM Beierfeld GmbH
Am Gewerbepark 9 • D – 08344 Grünhain-Beierfeld
Tel.: +49 3774 58 – 0 • Fax: +49 3774 58 – 545
manotherm.com • mail@manotherm.com

3202


04/16

Process Connection Dry Genic (PADG) and Dimensional Data (in mm)

Process Connection Dry Genic (PADG) and Dimensional Data (in mm)


PADG 7340v... ISO 2852

for tubes according to ISO 2037 and BS 4825



DN	PN	For tube male-Ø x wall thickness	Tube female-Ø	b	D	D1	dM	h
38	16	38 x 1.2	35.6	20	50.5	101	36	95
51		51 x 1.2	48.6		64			
63.5		63.5 x 1.6	60.3		77.4			
76.1		76.1 x 1.6	72.9		91			


PADG 7340.1v...DIN 32 676, series A for tubes according to DIN 11 850



DN	PN	For tube male-Ø x wall thickness	Tube female-Ø	b	D	D1	dM	h
40	16	41 x 1.5	38	20	50.5	101	36	95
50		53 x 1.5	50		64			
65		70 x 2	66		91			
80		85 x 2	81		106			

PADG 7340.6v... Tri-Clamp

for tubes according to BS 4825 and O.D.-Tube; ASME BPE and ISO 1127



NPS	DN	PN	For tube male-Ø x wall thickness		For tube female-Ø		b	D	D1	dM	h
			BS 4825 and O.D.-Tube / ASME BPE	ISO 1127	BS 4825 and O.D.-Tube / ASME BPE	ISO 1127					
1½"	38	16	38.1 x 1.6	42.4 x 2	34.8	38.4	20	50.5	101	36	95
2"	51		50.8 x 1.6	48.3 x 2	47.5	44.3		64			
2½"	63.5		63.5 x 1.6	60.3 x 2	60.3	56.3		77.5			
3"	76.1		76.2 x 1.6	76.1 x 2	73.0	72.1		91			